Over the years, Abritek Doors and Windows has always stood out from the industry standard with their innovative and high-end products that meet todays and tomorrow's needs. Continuous improvement and rapid tailoring to our customers' expectations represent our way of mastering the art of production.



A family business since 1947!

Abritek Doors and Windows provides a qualified customer service which is intended to be fast and efficient.

Warranty and Services

The best warranty in the industry

- PVC: 20 years
- Sealed Unit: 10 years
- Mecanism: 10 years
- Hardware: 10 years
- Labour: 1 year



Accreditations









Reaches energy efficiency (ER) of 37 in double glass.

Find your retailer and more information on Abritek.ca



DISTRIBUTED BY










Timeless Patio Door


The INOVA Patio Door integrates high performance and aesthetic. With a modern design or classic style, it will adapt to all projects depending on chosen options. It offers a refined style that maximizes brightness, and its maintenance is facilitated by a cover of resistant anodized threshold. Its performance will help you face the reality of our climatic variations. A product entirely manufactured at our plant to ensure the highest standard of quality.







Configure to your taste









- Height of 8': 70 ¾" x 95" 58 ½" x 81 ½" 82 ¾" x 95" 70 3/8" x 81 1/8"
- 94 ¾" x 95" 103 ¼" x 95" 103 ¼" x 81 ½" 115 ¼" x 95" 115 ¼" x 81 ½" 139 ¼" x 81 ½" 139 ¼" x 95"

Dimensions

Custom Dimensions | Transoms and Side Panels

Features

- Frame ALL PVC 7 1/4", J 3/4" integrated or HYBRID 7 5/16" Aluminum/PVC frame, integrated J 3/4"
- Standard aluminum color Black, White and Commercial Brown
- Welded PVC opening shutter with two steel reinforcements
- Structural mullion with steel reinforcement
- Anodized aluminum sill cover
- Stainless steel double-point mortise lock
- Beading system to fix the thermos
- Double energy glass thermos + argon gas
- Robust 45° extruded aluminum mosquito net

Options

- Triple glass thermos, 1 or 2 energy + argon gas
- Brick or cladding molding with extension anodized threshold
- Interior extension available up to 16 3/16"
- Foot lock
- Key lock
- Tinted glass
- Exterior aluminum color: Clear anodized
- Unlimited choice of colors

Handles

Standard:

- Crest model Colors: White, Black, Brushed nickel

- Optional: ■ Involute model
- Indoor/Outdoor
- Color: White

Moldings





necessary strength for the operation of the patio door. The system raises the shutter when the opening, slides without friction to rest it on the seals when closing. The security and tightness of the door are

guaranteed by 3 anchor points while the materials offer increased protection against corrosion.

Lift-and-slide Patio Door

The contemporary handle offers an optimal clearance in use. It is offered with black or stainless steel finish and handle 2-sided lift also includes a key lock.

Maximize the panoramic effect of your patio door with large dimensions in 2 sections thanks to a very heavy load capacity door.





Allowing incomparable ease of operation, Lift-and-slide hardware further reduces by 50% the



Performances


The INOVA Patio Door was tested by independent laboratories (AIR-INS) and meets











Double point mortise lock

Very Robust

Design



Easy Installation


- Pre-drilled frame for easy installation.
- Clipped PVC jamb liner to cover installation screws.





Structural and Thermal

the harmonized standard AAMA/WDMA/CSA 101/I.S.2/A440. Also qualified for ENERGY STAR® (ER), the *INOVA* Patio Door meets following standards:











The **INOVA** Patio Door meets all ENERGY STAR® Canada standards with an Energy Rating (ER) of 37 with double glass and 42 with triple glass (no grid). Results may vary depending on type of insulated glass ordered. PVC profiles are produced with a special PVC powder formula that was developed to get an outstanding finish but also strong enough to face our rude